



# Ducted Gas Heating



# Whole home heating

### Did you know?

With Brivis Zoning technology you can heat any area in your home. You can even heat just a single zone, saving you money on your energy bill.



# Fast

It doesn't matter what the temperature is outside, your Brivis Ducted Gas Heater will warm up your whole home before you know it.



### Reliable

Brivis pioneered energy efficient Ducted Gas Heating. To complement a full range of 3, 4 and 5 star heaters you can now save up to 30% on your next energy bill with the StarPro 6 Ducted Gas Heater.



#### Efficient

For over 50 years Brivis has been heating and cooling Australian homes. Unmatched for reliability, some of our first heaters are still working today.

#### Brivis Performance Guarantee

Expert design and installation of comfort systems is essential in ensuring optimum operation and maximum performance.

The unique Brivisize<sup>™</sup> software enables designers, in consultation with you, to accurately select the perfect Brivis appliance for your home. After using the guide and having your Brivis product correctly installed and commissioned by a licensed professional, if the Brivis unit does not perform as it was designed to do, Brivis will repair or replace the Brivis appliance free of charge, or refund your money.

# Brivis – Australia's leading climate system

A reputation for innovation, reliability and quality for over 50 years has led to Brivis being recognised as the staple of Ducted Gas Heating in Australian homes.

Every Brivis heater is made for the Australian winter and is guaranteed to provide your home with warm, cosy air for many years. Our design and manufacturing process is accredited to the Australian Standard AS/NZS ISO9001, and our Ducted Gas Heaters come with warranties of up to 10 years.

In addition to producing world-class home climate systems, Brivis operates a National Customer Care Centre. Our knowledgeable staff are on hand to ensure total enjoyment of your new Brivis Ducted Gas Heater.

# **Ducted Gas Heating**

Brivis Ducted Gas Heating comprises a heating unit connected to a series of outlets via a system of ducts. Ductwork and outlets supplied by your installer are strategically placed throughout your home, either in the floor or ceiling. The position of the heating unit depends on your house.

The ducts which connect the outlets to the heating unit are neatly tucked away out of sight. A wall controller lets you set the temperature for the whole home or just one single room.

# How does Ducted Gas Heating work?

The Brivis Ducted Gas Heating system draws air from inside your home through the heater where it is warmed. A fan pushes it into the rooms of your home via the outlets and duct network, in the form of a steady, gentle supply of warm air.

The Brivis controller monitors the air temperature on a continual basis and controls the Brivis Ducted Gas Heating system to ensure a consistently warm temperature throughout the home. On our higher efficiency models, as the home heats up, the heater modulates the gas so only a small amount of energy is used to keep the space at your desired comfort level.

Once your home reaches your desired temperature the heater unit switches off. The fan then comes to a halt slowly, ensuring that all the remaining heat inside the unit is used.



Ask your local Brivis dealer to Brivisize<sup>™</sup> your home. Brivisize<sup>™</sup> is a unique online sizing tool, ensuring your home is measured up correctly and accurately for all Brivis heating and cooling solutions.

Backed by our Brivis Performance Guarantee, Brivisize™ is your answer for ultimate peace-of-mind.

# The more stars, the more you save

# Lowest running costs

## Star ratings explained

The star rating on your Ducted Gas Heater helps you compare how much gas your heater is actually using. It's an indicative guide that outlines the running cost of the heater in terms of annual energy usage.

The higher the star rating, the more energy efficient the heater is - meaning bigger annual savings on your running costs. On average, an increase of one star means energy usage savings of approximately 10 percent.



#Energy savings are compared to a standard 3.0 star Ducted Gas Heater. Running Cost Data is based on Australian Standard AS4556-2011. House Heat Load 0.2MJ/HR/m3 and 600 Hours of operation (100 days at 6 hours per day). Annual Energy Consumption - as per AGA Star Ratings for Ducted Gas Heating Systems. Gas Price = 1.6 cents per MJ/HR). Savings based on Average House Floor Area for New Homes built in 2012 - 2013\* with 2.4m ceiling. Actual savings may vary due to variations in factors such as fuel costs, house size, thermal insulation and heater usage patterns. \* Source: Australian Property Investor, ABS, Commsec: November 2013

## Energy savings per annum<sup>\*</sup>

# StarPro 6 **Universal Series**

MEN

Introducing Brivis' highest efficiency Ducted Gas Heater, the SP6 series. The new range of Brivis 6 Star heaters is cleverly engineered to use less gas then traditional Ducted Gas Heaters. This is achieved through Quatrra™ technology, a superior 4 Pass Heat Exchanger with Modulating Gas Valve - meaning you get superior temperature control and greater efficiency.

Your 6 star gas heater is zone ready for up to 4 zones. Brivis ZonePlus™ allows you to set different temperatures in each zone or to turn off the zones you are not using, saving you money on your running costs. With Brivis ICE<sup>™</sup> compatibility, your 6 Star heater can be your ultimate gas heating and refrigerated cooling solution all year round. Selected models are also available in Universal Liquefied Petroleum Gas (ULPG).



# **Features**

- Universal Internal/external application
- Highest possible gas energy star rating Reduced running costs
- Reduced carbon emissions
- Brivis ICE<sup>™</sup> compatible ZonePlus™ compatible
- Zone-ready for up to four zones .

Energy Star Partner only applicable in New Zealand. Applies to SP6 range, not including SP615U





- Selected models available in ULPG
- Lay down kit (Internal application)
- Five year parts and labour warranty





USE THIS LABEL TO COMPARE DIFFERENT MODEL CENTRAL HEATERS Gas Ass



Save 30% annually compared to a standard 3 Star Ducted Gas Heater



# Compact and efficient



# StarPro 5 **Universal Series**

NEW

Brivis' latest 5 Star non-condensing range of Ducted Gas Heaters delivers excellent efficiency while using less gas to heat your home, all without the need for condensate drains. Brivis can now not only deliver a 5 Star rating without producing condensate, but can offer a cheaper way to get 5 Star efficiency without compromising on quality.

A non-condensing Ducted Gas Heater makes the system easier and faster to install, making it a great option for a new installation or to replace your old heater - meaning lower installation costs.

Brivis SP5 series is also ZonePlus™ and DualComfort<sup>™</sup> compatible.

# **Features**

- Universal Internal/external application
- Non-condensing 5 Star Rating
- High efficiency
- Cheaper and easier to install
- Brivis ICE™ compatible
- ZonePlus<sup>™</sup> compatible
- Zone-ready for up to four zones
- Lay down kit (Internal application)
- Five year parts and labour warranty









Save 22% annually compared to a standard 3 Star Ducted Gas Heater

## StarPro 4 **Universal Series**

The new and improved Brivis SP4 boasts up to an impressive 4.8 Star energy efficiency rating, making it one of the highest rated 4 Star Ducted Gas Heaters available.

Due to its flexible installation options the SP4 series is perfect for upgrading your old Ducted Gas Heater. It is an ideal all-round gas heater that's affordable, incredibly efficient and compact.

Brivis SP4 series is also ZonePlus™ and DualComfort<sup>™</sup> compatible.

# **Features**

- Outstanding efficiency up to 4.8 Stars
- Economical to run
- Brivis ICE<sup>™</sup> compatible
- ZonePlus<sup>™</sup> compatible
  - Zone-ready for up to four zones
  - Lay down kit (Internal SP415/SP421)
  - Five year parts and labour warranty





\*Energy savings are compared to a standard Brivis Buffalo. Running Cost Data is based on Australian Standard AS4556-2011. House Heat Load 0.2MJ/HR/m3 and 600 Hours of operation (100 days at 6 hours per day). Annual Energy Consumption - as per AGA Star Ratings for Ducted Gas Heating Systems. Gas Price = 1.6 cents per MJ/HR). Savings based on Average House Floor Area for New Homes built in 1995, with 2.4m ceiling. Actual savings may vary due to variations in factors such as fuel costs, house size, thermal insulation and heater usage patterns. \* Source: ABS 1301.0 Year Book Australia 2005

Compact and affordable



Universal internal/external application





USE THIS LABEL TO COMPARE DIFFERENT MODEL CENTRAL HEATERS



Save 13% annually compared to a standard 3 Star Ducted Gas Heater



# Next generation Classics

# 35+ years of performance

# Compact **Classic Range**

The Compact Classic range (CC3), as the name suggests, is a compact design for easy installation indoors and in tight spaces. Perfect for new homes, the CC3 is a price conscious, no fuss solution that's easy to install.

## **Features**

- Excellent value for money
- Three speed fan
- Up to 3.5 star rating
- Low profile, compact and splittable
- Suitable for Brivis ICE Add On
- Three year parts and labour warranty

# **Brivis Wombat Classic**

The Brivis Wombat is known for its performance and reliability and has a model to suit virtually any home. The Brivis two-piece Wombat range of heaters have up to 3.8 Star energy rating, making it one of the highest rated 3 Star Ducted Gas Heaters on the market - the best value option in its class.

### Features

- Easy to install
- Splittable for easy handling
- Suitable for Brivis ICE Add On
- Five year parts and labour warranty





#### **Brivis Buffalo BX3** If you are one of the thousands of Australians who have enjoyed the performance and reliability of a Brivis Ducted Gas Heater, chances are you are familiar with the Brivis Buffalo Classic heater. After all, there are more Brivis

Classic Ducted Gas Heaters installed in Australian homes than any other brand. With models to suit virtually all types of homes, the upgraded Brivis Buffalo external weatherproof units offer greater efficiency and have been reliably keeping Australians warm for over 35 years.

Perfect for those looking to replace their existing heater with an unrivalled dependable low cost option, the Classic series has proven performance and a name you can trust.

## Features

- Excellent value for money
- Easy changeover
- Reliable and built to last
- Superior airflow
- Five year parts and labour warranty

# **Brivis Buffalo BX5**

The new Brivis Buffalo 5 Star Heater has been designed with efficiency and reliability in mind. The energy efficient Brivis Buffalo 5 star is the perfect solution for replacing or upgrading your existing Buffalo. With savings of \$331\* on annual running costs compared to a standard Brivis Buffalo, the Brivis Buffalo 5 star is a simple upgrade choice. Your investment in the Brivis Buffalo 5 star is sure to provide you many years of trouble free, high efficiency comfort, as well as reduced gas consumption.

# Features

- High Efficiency 5 Star rating
- Easy to install

\*Energy savings are compared to a standard Brivis Buffalo. Running Cost Data is based on Australian Standard AS4556-2011. House Heat Load 0.2MJ/HR/m3 and 600 Hours of operation (100 days at 6 hours per day). Annual Energy Consumption - as per AGA Star Ratings for Ducted Gas Heating Systems. Gas Price = 1.6 cents per MJ/HR). Savings based on Average House Floor Area for New Homes built in 1995, with 2.4m ceiling. Actual savings may vary due to variations in factors such as fuel costs, house size, thermal insulation and heater usage patterns. \* Source: ABS 1301.0 Year Book Australia 2005



• Zone Plus compatible - up to 4 Zones • Five year parts and labour warranty





The Brivis Buffalo is the perfect upgrade and excellent value for money

# DualComfort

cycle systems.

# Considering cooling? You should read this.

The Brivis StarPro series of Ducted Gas Heaters provide the flexibility to seamlessly integrate a Brivis ICE™ (Integrated Cooling Equipment) refrigerated system, all while using the exact same ductwork and grilles - saving you both time and money. We call this technology Brivis DualComfort<sup>™</sup>.

The Brivis DualComfort<sup>™</sup> whole of home Ducted Gas Heating and refrigerative cooling solution allows you to create that

perfect feeling of comfort throughout your home. DualComfort<sup>™</sup> provides both refreshing, refrigerated cooling, or comfy gas heating. The technologies used in the DualComfort<sup>™</sup> heating and cooling solution combines a StarPro series Ducted Gas Heater with Brivis ICE™ - and are a culmination of 50 years of Brivis heating and cooling experience in Australia.

# What makes DualComfort<sup>™</sup> ducted air conditioning so attractive?

- Fully integrated gas heating and Brivis ICE™ refrigerated cooling system. The best of both worlds
- Staggered installation options allowing you to install heating first and cooling later, lowering your initial upfront cost
- · Common ductwork and grilles for both heating and cooling to rooms, meaning low cost installation
- · Flexibility to customise system for whole-of-home or zoned heating and cooling, meaning lower running cost
- Brivis Touch and NC-6 Networker controllers have built in zoning functionality which is simple and easy to use

When installing a Brivis ICE<sup>™</sup> Add-on refrigerated cooling system to an existing Ducted Gas Heating system, care must be taken to ensure the duct system is sized and designed correctly. If you are installing a heating system and plan to install Brivis ICE<sup>M</sup> Add-on refrigerated cooling system at a later date, then ensure that you advise your dealer and they will size the system accordingly.

\*In some Dual Comfort applications a Constant Zone may be required. Consult your specialist dealer for more information.

# DualComfort<sup>™</sup> product features

- ZonePlus<sup>™</sup> compatible (StarPro heaters only)
- Advanced control options
- Australian designed, locally made for more than 50 years
- Brivis ICE<sup>™</sup> Add-On refrigerated cooling system
- · Electronic ignition and integrated diagnostics
- Duct work installation flexibility (under floor or in roof space)
- Heating and cooling from the one controller



#### Keep your energy costs to a minimum

The combination of Ducted Gas Heating with refrigerative cooling provides a superior whole home climate control solution at an affordable rate.

#### The ultimate form of air-conditioning

The system combines the best form of heating and the best form of cooling. It can be zoned, utilises common ductwork and allows you to maintain your desired level of comfort all year.

#### Better performance in cold ambient temperatures

When the outside temperature drops close to zero the Ducted Gas Heater of the DualComfort<sup>™</sup> heating and cooling solution outperforms electric reverse cycle systems. In colder weather, gas heating is more effective and more comfortable, as the heat output of gas appliances is not affected by low ambient temperatures, which is the case with reverse



# **Flexible installation options**

With the DualComfort<sup>™</sup> heating and cooling solution you can install both the gas heating and refrigerated cooling at the same time, or install just the heating first, ready for the cooling to be added in at a later date. Simple. Ask your installer about being Brivis ICE<sup>™</sup> ready

# Take a closer look



Guardian™



# **Engineered for total comfort**

Brivis has been providing heating and cooling solutions to Australian homes for over 50 years. Our local manufacturing facility, located in Braeside Victoria, employs over 200 dedicated people and is home to some of Australia's most innovative

Brivis pioneered the very first 5 Star Ducted Gas Heater and has been instrumental in introducing some of the newest and most efficient systems in Australia including the Contour Evaporative Cooler and the new 6 star Ducted Gas Heater with Quattra™ technology. In fact, some of our very first gas heaters are still in operation today, nearly 50 years on. That's why Brivis has been benchmarked for



# Zoning made easy

#### Control

# Climate

With ZonePlus™, choose your climate for any room in the house, from anywhere in the house. You have the flexibility to cater to everyone's ideal climate level anytime of the day.

ZonePlus™ allows total control of all zones in your home no matter where you are. Control different climate levels in different zones, optimise heating up and cooling down times, have total control of your comfort and energy use. Even switch zones off. You're in control.

#### Comfort

Everyone's comfort levels are different and ZonePlus<sup>™</sup> has taken this on board. No matter what your comfort level is, each zone is completely within your control. A controller in every zone allows easy management.

# **Introducing Brivis Zoning Solutions**

#### 1. ZonePlus™

For outstanding individual comfort, control and energy management, ZonePlus™ allows you to have up to four individually controlled zones, each with their own time and temperature settings.

For total flexibility, you can upgrade as many Brivis Temperature Sensors to Brivis NC6 or Touch controllers remote allowing you to fully control, program and manage each zone – eliminating the need for you to go back to a Master controller. Adjust temperatures for each zone as it suits you from any controller in the home. Perfect comfort, absolute control.

ZonePlus™ works in unison with any Brivis StarPro Ducted Gas Heater with 4, 5 and 6 star efficiencies. It can also operate your Brivis DualComfort™ system for the ultimate, integrated heating and cooling comfort control solution.

#### 2. Adaptive Zoning

Allows heating or cooling to be used with one Brivis controller, operating a common zone, as well as up to four additional zones, e.g. lounge room, bedrooms, kitchen/ dining etc.

A Brivis NC6 or Touch can simply turn zones on or off to manage only those areas you are using.

# Benefits of ZonePlus<sup>™</sup>

#### Reduce your energy costs

Switching off unused zones not only helps reach your set temperature faster, but will also save you lots on your energy bill. Adjusting your comfort levels moderately can also make big changes to your energy bill.

#### Save money

A large home may require for example, a 20kW system, to effectively heat or cool the entire home. In consultation with a dealer, you may find that you will only ever use half your rooms at any one time - hence a 10kW system would suit. Providing a significant up-front cost saving and minimising running costs.

#### Get more comfortable quicker

With the option of Brivis controllers in every zone, you no longer need to rely on one central controller managing your entire home. Controlling your climate is only ever a few steps away. How convenient is that?

\*In some Dual Comfort applications a Constant Zone may be required. Consult your specialist dealer for more information.





#### Brivis Touch<sup>™</sup>



#### Brivis NC6 Networker™



**Remote Temp Sensor** 

# Servicing

# Controllers

# **Quality Service For Over 50 Years**

Brivis products are renowned for their quality, performance and reliability, and have been keeping Australians comfortable for over 50 years. Our commitment to producing exceptionally engineered, high quality products is supported by our manufacturer's warranty through factory-trained professionals, ensuring your ultimate protection and peace of mind.

The Brivis standard parts and labour product warranty is 5 years. Brivis offers the option of extending this warranty up to a further 4 years, for a total of 9-year parts and labour warranty, on Brivis Ducted Gas Heaters<sup>1</sup>. Furthermore, Brivis offers a 10 year warranty on the gas burner, heat exchanger and structural component.

Heating and cooling equipment is subject to normal wear and tear and often operates under extreme conditions. It is recommended that such appliances be serviced and maintained by qualified licensed technicians at a minimum of once every two years to prolong the life of the unit, help keep it running safely and at optimum efficiency.

# Brivis Service Advantage<sup>™</sup> Program

The optional 4 years parts and labour extended warranty is in addition to the standard 5 year Brivis parts and labour warranty, and is available when you elect to participate in the Brivis Service Advantage program.

The program is subject to terms and conditions, including registering your product with Brivis and completing the scheduled servicing.

# Up to 9 years warranty<sup>\*\*</sup> (5 year + 4 year extended)

Made from premium materials and built to last, Brivis provides a standard 5 year parts and labour warranty on all Brivis Ducted Gas Heaters<sup>1</sup>, plus an optional 4 years extended service warranty.



<sup>1</sup> Excludes Brivis CC3 models, which has 3 years parts + labour warranty \*\*Conditions apply, visit brivis.com.au for full terms and conditions.



#### We're at your Service

The National Customer Care Centre provides first class service and maintenance of your system, ensuring it's running at its highest efficiency - so you can enjoy the Brivis experience for many years to come.

Operating 5 days a week, 8:00am to 5:30pm EST, Monday to Friday.

1stCare: 13 43 73

#### **Program Benefits**

- · Covers eligible Brivis products irrespective of where they are purchased
- Factory-direct service; deal with the manufacturer
- Factory-trained, licensed technicians
- Comprehensive 'log book' type service
- Up to 9 years parts and labour warranty

# **Brivis Touch**<sup>™</sup>

The Brivis Touch™ is the latest innovation in climate control, allowing you to create total home comfort with pure simplicity.

The ability to control your Brivis Ducted Gas Heater, Evaporative Cooler and Dual Comfort system is at your fingertips with the sleek Brivis Touch™, high-resolution colour touchscreen controller. It's that simple.

# Brivis NC6 Networker<sup>™</sup>

The Networker is designed with an easy-to-use rotary dial, an easy-to-read LCD screen and is backlit using Electro-Luminescence (EL) technology, making the screen easier to read in poorly lit areas or at night. The NC6 can operate both a Brivis ducted gas heater as well as a Brivis cooling system, providing total control.

# **Programmable Controller**

The Programmable Controller can operate in either auto or manual modes. To program you simply preset temperatures and times for the heating/cooling system to turn on and off. This Controller is also suitable for Brivis ICE™ system with the Classic Heater Range.

# Manual Controller

The Manual Controller is a simple to use heating only thermostat with a large easy to read digital display.

# Remote Temperature Sensor for ZonePlus<sup>™</sup>

For total flexibility when zoning your home a remote temperature sensor, when used with a Touch or Networker control, will help you manage and control temperatures throughout your home.





#### Brivis Touch<sup>™</sup> Features

- Simplicity at its best
- Secure, 7 day programmability
- Customised zone control
- Status monitor and notifications
- ZonePlus<sup>™</sup> compatible









# Specifications\*

| Brivis Duct                        | ted Gas Heater | Star Rating | Capacity (kW) | Airflow (L/s) @ 100Pa ESP | Dimensions (L x W x H)               | Net Weight (kg) | Available in LPG / ULPG |  |
|------------------------------------|----------------|-------------|---------------|---------------------------|--------------------------------------|-----------------|-------------------------|--|
|                                    |                |             |               | StarPro SP6 Series        |                                      |                 |                         |  |
| SP615UN                            |                | 6.0         | 15            | 630                       | 991x428x658                          | 62              | -                       |  |
| SP623UN                            |                | 6.0         | 23            | 683                       | 991x428x658                          | 64              | -                       |  |
| SP623UN XA                         |                | 6.0         | 23            | 723                       | 991x428x658                          | 64              | ULPG                    |  |
| P630UN                             |                | 6.0         | 30            | 1025                      | 1083x550x707                         | 86              | -                       |  |
| P630UN XA                          | A              | 6.0         | 30            | 1055                      | 1083x550x707                         | 86              | ULPG                    |  |
| SP635UN                            |                | 6.0         | 35            | 1103                      | 1083x550x707                         | 86              | ULPG                    |  |
| P521UN                             |                | 5.0         | 21            | StarPro SP5 Series        | 991 x 428 x 658                      | 61              |                         |  |
|                                    | ٨              | 5.0         | 21            | 770                       | 991 x 428 x 658                      | 61              |                         |  |
| SP521UN XA                         |                | 5.0         | 30            | 1078                      | 1083 x 550 x 707                     | 80              |                         |  |
| SP530UN                            |                | 5.0         | 30            |                           |                                      | 80              | -                       |  |
| SP530UN XA<br>SP535UN              |                | 5.0         | 35            | 1138                      | 1083 x 550 x 707<br>1083 x 550 x 707 | 80              | -                       |  |
| -000014                            |                | 5.0         | 30            | StarPro SP4 Series        | 1063 x 550 x 707                     | 80              | -                       |  |
| SP415UN                            |                | 4.1         | 15            | 555                       | 845x397x775                          | 65              | -                       |  |
| SP421UN                            |                | 4.8         | 21            | 555                       | 845x397x775                          | 65              | -                       |  |
| SP430UN                            |                | 4.2         | 30            | 953                       | 923x549x644                          | 84              | -                       |  |
| :P435UN                            |                | 4.3         | 35            | 1041                      | 923x549x644                          | 84              | -                       |  |
|                                    |                |             |               | Buffalo 5 Star Series     |                                      |                 |                         |  |
|                                    | 300mm base box | 5.1         | 20            | 545                       | 852 x 420 x 775                      | 57              | -                       |  |
| (520                               | 350mm base box |             |               | 609                       |                                      |                 |                         |  |
|                                    | 300mm base box |             |               | 972                       | 1028 x 580 x 866                     | 67              | -                       |  |
| (526                               | 350mm base box | 5.0         | 30            | 1042                      |                                      |                 |                         |  |
|                                    |                |             |               | Compact Classic Series    | 5                                    |                 |                         |  |
| C315IN                             |                | 3.0         | 15.0          | 500                       | 724 x 411 x 604                      | 52              | LPG                     |  |
| C320IN                             |                | 3.5         | 19.5          | 500                       | 724 x 411 x 604                      | 53              | LPG                     |  |
| C320IN-XA                          | ł              | 3.5         | 19.5          | 570                       | 724 x 411 x 604                      | 53              | LPG                     |  |
| C325IN                             |                | 3.1         | 23.5          | 560                       | 724 x 411 x 604                      | 53              | LPG                     |  |
| C325IN-XA                          | A              | 3.1         | 23.5          | 620                       | 724 x 411 x 604                      | 53              | LPG                     |  |
| CC330IN                            |                | 3.3         | 30.0          | 940                       | 843 x 564 x 640                      | 71              | LPG                     |  |
| C330IN-XA                          |                | 3.3         | 30.0          | 1000                      | 843 x 564 x 640                      | 71              | LPG                     |  |
|                                    |                |             |               | Classic Series            |                                      |                 |                         |  |
| P Wombat 15N                       |                | 3.8         | 15.5          | 412                       | 1187 x 412 x 704                     | 52              | -                       |  |
| P Wombat                           |                | 3.8         | 21.0          | 487                       | 1187 x 412 x 704                     | 55              | -                       |  |
| P Wombat                           |                | 3.8         | 21.0          | 519                       | 1187 x 412 x 704                     | 55              | -                       |  |
| P Wombat                           |                | 3.7         | 28.0          | 885                       | 1265 x 538 x 813                     | 67              | _                       |  |
| P Wombat 26N XA                    |                | 3.7         | 28.0          | 974                       | 1265 x 538 x 813                     | 67              | _                       |  |
| (315                               | 300mm base box | 3.9         | 15.5          | 461                       | 850 x 420 x 775                      | 56              | -                       |  |
|                                    | 300mm base box |             |               | 541                       |                                      | 57              | -                       |  |
| 3X320                              | 350mm base box | 3.8         | 20.0          | 574                       | 850 x 420 x 775                      |                 |                         |  |
|                                    | 350mm base box |             | 28.0          | 849                       |                                      | 67              | -                       |  |
| BX326                              | 400mm base box | 3.5         |               | 957                       | 1030 x 579 x 894                     |                 |                         |  |
| 400mm base box<br>Downflow DF320XA |                | 3.7         | 18.2          | 575                       | 461 x 398 x 1305                     | 58              | -                       |  |
| ownflow D                          | FJZUXA         |             |               |                           |                                      |                 | 1                       |  |
| ownflow D<br>oflow UF32            |                | 3.9         | 17.8          | 500                       | 511 x 398 x 1210                     | 55              | -                       |  |

All Brivis Classic heaters are Brivis Networker NC6 & Touch compatible, but require an interface to be fitted at additional cost. Brivis Touch & Networker NC6 not compatible with Brivis ICE<sup>™</sup> Add-on refrigerated cooling systems on Brivis Classic Heaters. Brivis Classic heaters do not have on-board Add-On Cooling connections as standard.

|                            |  |                     | Add on ICE <sup>™</sup> - | DualComfort™               |                      |                             |                     |                   |  |  |
|----------------------------|--|---------------------|---------------------------|----------------------------|----------------------|-----------------------------|---------------------|-------------------|--|--|
|                            | System Overview  |                     | 10                        | 13                         | 15                   | 17                          | 18                  | 22                |  |  |
| Power Supply               |  |                     |                           | 220~240-1-50               |                      |                             |                     | 415-3-50          |  |  |
| Mode                       |  |                     | Inverter                  |                            |                      |                             | Conventional        |                   |  |  |
|                            | Nominal Capacity                                       | kW                  | 10                        | 13                         | 15                   | 17                          | 18                  | 22                |  |  |
|                            | Rated Capacity   | kW                  | 10.1                      | 13.07                      | 14.57                | 16.24                       | 17.1                | 21.1              |  |  |
| Cooling Capacity           | Capacity Range   | kW                  | 4.8 ~ 11.0                | 6.3 ~ 14.0                 | 7.5 ~ 16.0           | 8.3 ~ 16.6                  | N                   | /A                |  |  |
|                            | Rated Input  | W                   | 3.20                      | 4.08                       | 4.67                 | 5.18                        | 5.12                | 5.70              |  |  |
|                            | AEER   |                     | 3.12                      | 3.20                       | 3.12                 | 3.13                        | 3.33                | 3.70              |  |  |
|                            | ICE™ Outdoor Unit                                      |                     | DONSC10Z71                | DONSC13Z71                 | DONSC15Z71           | DONSC17Z71                  | DO-SC18Z9           | DO-SC22Z9         |  |  |
| Power Supply               |  | V-ph-Hz             |                           | 220~2                      | 40-1-50              |                             | 400~4               | 15-3-50           |  |  |
| Maximum Input Current      |  | A                   | 18.0                      | 23.0                       | 25.0                 | 27.0                        | 20.9                | 20.9              |  |  |
| Compressor                 |  | Туре                | Rotary                    | Rotary                     | Rotary               | Rotary                      | Scroll              | Scroll            |  |  |
| Sound Pressure Level @1m   | 1  |                     | 61                        | 62                         | 62                   | 62                          | 61                  | 61                |  |  |
| Sound Power Level          |  | dB(A)               | 70                        | 71                         | 71                   | 71                          | 70                  | 70                |  |  |
| Dimensions                 | Dimensions (L x W x H)                                 | mm                  | 946 x 410 x 810           | 952 x 415 x 1333           | 952 x 415 x 1333     | 952 x 415 x 1333            | 1258 × 450 × 1390   | 1258 × 450 × 1390 |  |  |
| DITIENSIONS                | Net Weight   | kg                  | 68.5                      | 100                        | 116                  | 130                         | 161                 | 161               |  |  |
|                            | Refrigerant  | Туре                | R410A                     |                            |                      |                             |                     |                   |  |  |
|                            | Gas Connection Size                                    |                     | 15.9                      | 19.0                       | 19.0                 | 22.2                        | 22.2                | 28.6              |  |  |
|                            | Liquid Connection Size                                 | mm                  | 9.5                       | 9.5                        | 9.5                  | 12.7                        | 12.7                | 12.7              |  |  |
|                            | Recommended Interconnecting                            | 1 - 10m             | - 15.9                    | 19.0                       | 19.0                 | 22.2                        | 22.2                | 28.6              |  |  |
|                            | Pipe Size - Gas (mm)                                   | 10 - 30m            |                           |                            |                      |                             | 28.6                | 28.6              |  |  |
| Refrigerant Piping         | Recommended Interconnecting<br>Pipe Size - Liquid (mm) | 1 - 10m             | 0.5                       | 9.5                        | 9.5                  | 12.7                        | 9.5                 | 12.7              |  |  |
|                            |  | 10 - 30m            | 9.5                       |                            |                      |                             | 12.7                | 12.7              |  |  |
|                            | Precharged Length                                      | m                   | 15                        | 15                         | 15                   | 15                          | 15                  | 15                |  |  |
|                            | Max. Pipe Length                                       |                     | 65                        | 65                         | 65                   | 55                          | 30                  | 30                |  |  |
|                            | Max. Height Diff (CDU below)                           |                     | 30                        | 30                         | 30                   | 30                          | 8                   | 8                 |  |  |
|                            | Max. Height Diff (CDU above)                           |                     | 30                        | 30                         | 30                   | 30                          | 8                   | 8                 |  |  |
| Ambient Temperature Limits |  | °C                  | -15 ~ 50                  | -15 ~ 50                   | -15 ~ 50             | -15 ~ 50                    | -5 ~ 46             | -5 ~ 46           |  |  |
|                            | ICE <sup>™</sup> Indoor Unit                           |                     | DINLU10Z7                 | DINLU13Z7                  | DINLU15Z7            | DINXU17Z7                   | DI-XU18Z            | DI-XU22Z          |  |  |
| Power Supply               |  | V-ph-Hz             |                           | 220~2                      | N/A                  |                             |                     |                   |  |  |
| Description                |  | Туре                |                           | C                          | Compact Coil with Ro | und Duct Connectior         | ns                  |                   |  |  |
| Airflour                   | Rated  |                     | 678                       | 697                        | 830                  | 956                         | 920                 | 992               |  |  |
| Airflow                    | Minimum  | L/s                 | 500                       | 550                        | 620                  | 850                         | 750                 | 900               |  |  |
| Coil Static Pressure Drop  | @ Rated Airflow (Dry / Wet)                            | Pa                  | 48 / 58                   | 50 / 60                    | 65 / 80              | 92 / 122                    | 138 / 173           | 101 / 127         |  |  |
| Coll Static Pressure Drop  | @ Minimum Airflow (Dry / Wet)                          |                     | 33 / 38                   | 35 / 40                    | 48 / 60              | 73 / 98                     | 91/114              | 82 / 103          |  |  |
| Dimensione                 | Dimensions (L x W x H)                                 | mm                  | 823 x 540 x 678           | 823 x 540 x 678            | 823 x 540 x 678      | 777 x 811 × 549             | 680 × 627 × 542     | 777 x 748 × 549   |  |  |
| Dimensions                 | Net Weight   | kg                  | 31                        | 31                         | 40                   | 42                          | 36                  | 41                |  |  |
| Duct Connection (Outlet)   |  |                     | Ф400                      | Ф450                       | Ф450                 | Ф450                        | Ф450                | Φ500              |  |  |
| Duct Connection (Inlet)    |  |                     | Ф400                      | Ф400                       | Ф400                 | Ф400                        | Ф400                | Ф450              |  |  |
| Condensate Drain Connecti  | on   | mm                  | 20                        | 20                         | 20                   | 20                          | 20                  | 20                |  |  |
| Refrigerant Pipe           | Gas  |                     | 15.9                      | 19.0                       | 19.0                 | 22.2                        | 22.2                | 28.6              |  |  |
| Connections                | Liquid   |                     | 9.5                       | 9.5                        | 9.5                  | 12.7                        | 12.7                | 12.7              |  |  |
| Operating Temperature Lim  | its  | ٥C                  | 19 ~ 32                   | 19 ~ 32                    | 19 ~ 32              | 19 ~ 32                     | 17 ~ 32             | 17 ~ 32           |  |  |
|                            | ance with AS3823 with 5m charged length. With          | h our policy of con | tinuous improvement. we   | reserve the right to chang |                      | ne, specifications or desig | Ins without notice. | I                 |  |  |

|                 |                               | Brivis ICE™ Conventional           |                 |                                 |                                |              |
|-----------------|-------------------------------|------------------------------------|-----------------|---------------------------------|--------------------------------|--------------|
| Heater Range    | 10                            | 13                                 | 15              | 17                              | 18                             | 22           |
| SP6U            | SP615U                        | SP623U, SP623U XA (Ext)            | SP623U XA (Int) | SP630U, SP630U X                | P630U, SP630U XA, SP635U (Ext) |              |
| SP5U            | -                             | - SP521U, SP521U XA (Ext) SP521U X |                 | SP530U, SP530U XA, SP535U (Ext) |                                | SP535U (Int) |
| SP4U            | SP415U, SP421U                | -                                  | SP430U          | SP435U                          | -                              | -            |
| BX5             | BX520 XA                      | -                                  | -               | BX526                           | BX526 XA,                      | -            |
| Classic         | BX320 XA, 2PW20N XA           | -                                  | BX326           | BX326 XA, 2PW26N                | 2PW26N XA                      | -            |
| Compact Classic | CC315, CC320, CC320 XA, CC325 | CC325 XA                           | CC330, CC330 XA | -                               | -                              | -            |

\*With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice.

Note: All images are for illustration purposes only.



For all sales and service enquiries:

# **Plum Heating & Cooling**

Unit 4, 22-30 Wallace Avenue Point Cook, Victoria 3030 Telephone: 03 8360 9622 Email: contact@plumheatcool.com.au www.plumheatcool.com.au

**Brivis Australia Pty Ltd** ABN 64 096 079 088

61 Malcolm Road, Braeside, Victoria 3195

PO Box 280, Braeside, Victoria 3195

For further information visit www.brivis.com.au or call 1300 274 847

#### **Rinnai New Zealand**

105 Pavilion Dr, Mangere, Auckland 2150, New Zealand,

www.rinnai.co.nz Ph +64 9 257 3800



**TOTAL HOME COMFORT** 





COOLING